

OMI OPTIKA Engineering Ltd.

2018 CATALOG






Engineering Ltd.

OMI OPTIKA Mérnökiroda Kft.




www.omi-optika.hu info@omi-optika.hu tel.: +36 1 392 2208


LED Ring Lights



Working example



Standard Ring Light



Large Area Ring Light



UV Ring Light, 395nm

LED Ring Lights provide direct illumination with high and even intensity on specular or opaque surfaces. Beam angle is factory adjusted according to customers' demand on working distance (WD) and illuminated area size.

Specifications:

- white, UV, blue, green, red or NIR light
- power requirement: 12V DC or 24V DC (please specify when ordering)
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu or plastic housing
- designed to operate in harsh industrial environment
- please call for IP classified versions

LED Ring Lights

Product Number	Dimensions (mm)	Light emitting surface (mm)	Wave- length (nm)	Available IP protection
3-057-000	Ø100/Ø60x29	Ø100/Ø60	white	IP65
3-060-000	Ø100/Ø45x30	Ø100/Ø45	white	IP65
3-063-000	Ø80/Ø50x30	Ø80/Ø50	375	IP65

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.




White Ring Light




High power white Ring Light

OMI OPTICS Engineering Ltd

ED Darkfield Lights





Typical dimensions





LED Darkfield light

LED Darkfield (Low Angle) Lights are suitable for highlighting surface roughnes, surface structure, edges with the help of light nearly parallel with the surface.

Specifications:

- white, UV, blue, green, red or NIR light
- power requirement: 12V DC or 24V DC (please specify when ordering)
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu or plastic housing
- designed to operate in harsh industrial environment
- please call for IP classified versions


LED Darkfield (Low Angle) Ligths

Product number	Dimensions (mm)	Illuminated area (mm)	Wave- length (nm)	Available IP protection
3-067-000	100x100x10/∅60	Ø60	640	IP65
3-077-000	150x150x10/Ø100	Ø100	640	IP65
3-078-000	150x150x10/Ø100	Ø100	850	IP65


More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.


OMI OPTICS Engineering Ltd




LED Dome Lights




LED Dome Light



LED Low-Angle Dome Light



LED Dome Light typical dimensions



LED Low-Angle Light typical dimensions

LED Dome Lights ensure even, shadowless illumination for inspecting specular, uneven or curved surfaces. Shadows and reflections generated by the surface can be avoided this way.

Specifications:

- white, UV, blue, green, red or NIR light
- power requirement: 12V DC or 24V (please specify when ordering)
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu housing
- designed to operate in harsh industrial environment

LED Dome Lights					
Product number	Dimensions (mm)	Illuminated surface (mm)	Wavelength (nm)		
3-087-000	Ø70/Ø30x40	Ø50	White		
3-090-000	Ø122/Ø80x60	Ø80	White		

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.







White compact LED Dom Light OMI 3-090-000

OMI OPTICS Engineering Ltd.

LED Coaxial Lights



LED Coaxial Lights



Typical dimensions



30x30 LED Coaxial Light



100x50 LED Coaxial Light

LED Coaxial Lights ensure even, diffuse, axial illumination for inspecting glossy surfaces.

Specifications:

- white, UV, blue, green, red or NIR light
- power requirement: 12V DC or 24V DC (please specify when ordering)
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu housing
- designed to operate in harsh industrial environment


LED Co	LED Coaxial Lights				
Product number	Dimensions (mm)	Light emitting surface (mm)	Wavelength (nm)		
3-304-000	110x100x60	100x50	640		
3-305-600	40x40x90	30x30	640		
3-310-600	40x40x73	30x30	420		
3-320-600	80x110x40	29x73	420		

More standard and custom versions are available.


For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.

OMI OPTIKA Mérnökiroda Kft. info@omi-optika.hu JMI OPTICS Engineering Ltd.

Standard LED Backlights




LED Back Lights



Typical dimensions





Slim Standard Backlights

Standard LED Backlights ensure homogen illumination to display contours of objects sized up to 100 mm with high contrast. Also applicable as diffuse lighting.

Specifications:

- white, blue, green, red or NIR light
- homogen intensity distribution
- power requirement: 12V DC or 24V DC (please specify when ordering)
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu housing
- glass or plastic illumination surface
- designed to operate in harsh industrial environment

Slim Standard Backlights:

- typical thickness: 8 to 10 mm
- illuminating area: <~50 mm x < ~50 mm

Thin Standard Backlights

- thickness: 12 mm
- illuminating area: <~50 mm x < ~50 mm

Thick Standard Backlights

- typical thickness: 20 mm
- illuminating area: <~100 mm x < ~100 mm


Standard LED Backlights

Product number	Dimensions (mm)	Light emitting surface (mm)	Wavelength (nm)	Available IP protection
3-201-000	100x100x20	80x80	640	IP65
3-124-000	40x40x12	24x24	red	IP65
3-125-000	50x40x12	34x34	red	IP65
3-148-000	33x40x8	24x24	red	IP65
3-216-600	170x220x16	150x200	white	IP65
3-216-700	100x300x16	80x280	white	IP65
3-220-000	50x65x20	35x60	white	IP65


More standard and custom versions are available.

OMI OPTICS Engineering Ltd

Large LED Backlights



Large LED Back Lights



Typical dimensions



Slim Large LED Backlight



Standard Large Backlight

Large LED Backlights ensure homogen illumination to display contours of objects larger than 100 mm with high contrast. Also applicable as diffuse lighting.

Specifications:

- white, blue, green, red or NIR light
- homogen intensity distribution
- power requirement: 12V DC or 24V DC (please specify when ordering)
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu housing
- plastic illumination surface
- designed to operate in harsh industrial environment
- please call for IP classified versions

Standard Large LED Backlights:

- typical thickness: 25 mm
- light emitting surface: >~100 mm x >~100 mm

Slim Large LED Backlights (edge-lit):

- typical thickness: 10 mm
- light emitting surface: >~100 mm x >~100 mm

Large L	Large LED Backlights				
roduct number	Dimensions (mm) sui		Wavelength (nm)		
3-207-000	130x190x25	100x160	Red		
3-212-000	200x200x30	200x150	White		
3-240-000	235x240x10	200x200	Red		
3-241-000	180x180x10	120x140	White		
3-242-000	133x113x10	100x80	White		
3-246-000	440x240x10	400x200	Red		
3-247-000	380x240x10	340x200	Red		

More standard and custom versions are available.


For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.

OMI OPTICS Engineering Ltd.

OMI OPTIKA Mérnökiroda Kft. info@omi-optika.hu

EL.: +36 1 392 2278 +36 30 950 113





LED SPOT Backlight



LED SPOT Backlight, diam. 40mm



LED SPOT Backlight, 40x40mm

LED SPOT Backligths offer extra large intensity for exposures in the microsecond range. Simple installation, no maintenance. Recommended also for limited space applications.

Specifications:


- white, blue, green, red or NIR light
- power consumption: max. 3 W
- homogene intensity distribution
- light emitting area: ø35 mm
- power requirement: constant current
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu housing
- dimensions: ø40/ø25x50 mm
- plastic or glass light emitting surface
- designed to operate in harsh industrial environment
- please call for IP classified versions

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.

RGB LED Spot Lights





RGB LED SPOT Light





RGB LED SPOT Lights

RGB LED SPOT Lights offer three separately controllable LED chips integrated into one compact modul. A wide range of visible color gamut or white light can be achieved with integrated color mixing optics. RGB LED SPOT Lights are also available in moduls to achive greater intensity.

Specifications:

- white or coloured light
- power consumption: max. 3 W
- beam angle: 30°
- power requirement: constant current
- separately adjustable intensity for each chip
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu housing
- compact size: ø25 x 50 mm
- fixing with M4 screw
- designed to operate in harsh industrial environment

Typical field of use:

- enhancing contrast depending on the color of the workpiece in machine vision inspection
- illumination with variable color at laboratory tests
- museum display cases
- artworks
- illuminations for photography

3x1W RGB LED SPOT Lights


Product number	Dimensions (mm)	Light emitting surface (mm)	Wavelength (nm)	Available IP protection
3-403-000	Ø25x45	Ø 2 4	RGB	IP65
3-411-000	Ø25x45+120 (goose neck)	Ø 24	RGB	IP65
3-460-600	Ø90xØ50x20	Illuminated area: Ø50	420 + White	

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.

OMI OPTIKA Mérnökiroda Kft. info@omi-optika.hu JMI OPTICS Engineering Ltd.

LED Spot Modul Lights



LED SPOT Light



9x3W RGB Modul Light



6x3W UV Modul Light

LED SPOT Modul Lights include multiple LED SPOT Lights offering extreme intensity with maintenance-free passive cooling and individually adjustable reflectors.

Specifications:

- power consumption: max. n x 3 W
- beam angle: from 10° up to 180°
- white, UV, blue, green, red, yellow or NIR light
- power requirement: constant current
- available with power supply with optional trigger input

LED SPOT Modul Lights					
Product number	Dimensions (mm)	Light emitting surface (mm)	Wavelength (nm)	Available IP protection	
3-402-200/ 1W/3W/5W	Ø80x87	Ø18,5x4pcs	any color	IP65	
3-456-000/ 1W/3W/5W	200x50x80	170x30	any color	IP65	

- continuous or strobe operation (depends on power supply)
- circle, ring or line layout
- > 50.000 h lifetime
- robust, anodized alu housing with robust fixing
- designed to operate in harsh industrial envinroment
- please call for IP classified versions

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.



4x3W White Modul Light

OMI OPTIKA Mérnökiroda Kft. info@omi-optika.hu JMI OPTICS Engineering Ltd.

TEL.: +36 1 392 2278 +36 30 950 113



LED Lights for Fluor



LED ringlight, 365nm, OMI 3-063-000



LED SPOT projector, 395nm OMI 3-426-700



LED Module light, 395nm OMI 3-461-000

LED Lights for Fluorescence Imaging

OMI LED Lights for fluorescence imaging are highly efficient sources of UV or dark blue lights required for getting effective and high contrast fluorescent images.

High power LED sources in fluorescent illuminators with lifetime over 50,000 hours offer a compact and economical alternative to formely used expensive arc lamps with limited lifetime.

We offer standard and custom spot, ring and axial lights as well as replacement units for former fiber optical light sources between 365-450nm. High pass optical filters are also available with our fluorescence light systems.

High power fluorescent axial lights and fiber optical replacement lights are fan cooled assuring continuous operation.

Specifications:

- UV or blue light (365, 395, 400, 420nm)
- power requirement: 24VDC or constant current
- available with specific power supply with optional trigger input
- continous or strobe operation
- > 50.000 h lifetime
- robust, anodized alu housing
- compact size
- designed to operate in harsh industrial environment

LED Lights for Fluorescence Imaging λ≤400nm (available also with λ>400nm)

Product number	Dimensions (mm)	Illuminated area (mm)	Wavelength (nm)
3-063-000	Ø80x30	Ø50	365
3-426-700	Ø20xØ60x20	Ø20-60	395
3-461-000	Ø125x55	Ø 60	395

More standard and custom versions are available.

escence Imaging



Coaxial LED Light, 420nm OMI 3-310-600

LED Lights for Fluorescence Imaging, λ>400nm (available also with λ≤400nm) Product Dimensions Illuminated area Wavelen


Product number	Dimensions (mm)	Illuminated area (mm)	Wavelength (nm)
3-460-600	Ø90xØ50x20	Ø50	420 + White
3-310-600	40x40x73	30x30	420
3-320-600	80x110x40	29x73	420
3-418-600	Ø55	fiber optics replacement	420
3-418-700	Ø25	fiber optics replacement	420

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.



Coaxial LED Light, 420nm OMI 3-320-600



LED Lights for fiber optic replacement, 420nm OMI 3-418-600 OMI 3-418-700








High power LED Ring Light, dual wavelength (white/420nm) OMI 3-460-600

_ED Spot Lights



LED SPOT Light



LED SPOT Lights



LED SPOT Light with gooseneck

LED SPOT Lights including one power LED offer high intensity for a wide range of application with maintenance-free passive cooling.

Specifications:

- white, blue, green, red or NIR light
- power consumption: max. 3 W
- beam angle: 8°, 30°, 50° or 10°x50°
- power requirement: constant current
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu housing
- compact size: ø25 x 50 mm
- fixing with M4 screw
- cable outlet on the side
- designed to operate in harsh industrial environment
- please call for IP classified versions

Typical field of use:

- products, workpieces
- laboratory tests
- machine vision measurements, calibrations
- microscopic inspections
- workpieces to be machined (eg. milling, lathing etc.)


LED SPOT Lights					
Product Dimensions Lig number (mm)		Light emitting surface (mm)	Wavelength (nm)	Available IP protection	
3-402-000/ 1W/3W/5W	Ø25x45	Ø18,5	any color	IP65	
3-410-000/ 1W/3W/5W	Ø25x45+120 (goose neck)	Ø18,5	any color	IP65	

More standard and custom versions are available.


For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.

OMI OPTIKA Mérnökiroda Kft. info@omi-optika.hu DIVITOPTICS Engineering Ltd


LED Spot Projectors



LED Spot Projector



Typical pattern



Projector for 3D scanning



LED SPOT Projector with fixed focus

OMI OPTIKA Mérnökiroda Kft. info@omi-optika.hu

LED SPOT Projector Lights illuminate workpieces of any size with a Structured Light. Usually optimised for a given distance, but also available with focusable optics.

We offer LED SPOT Projectors to project light spots with definite size or diamaters, or with any pattern e.g. for 3D scanning.

Specifications:

- power consumption: max. 3 W
- projecting distance: max. ~3 m
- white, blue, green, red or NIR light
- available with custom size or pattern (Structured Light)
- even intensity distribution
- power requirement: constant current
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply
- > 50.000 h lifetime
- robust, anodized alu housing
- compact size: ø25 x 50 mm
- fixing with M4 screw
- cable outlet on the side
- designed to operate in harsh industrial envinroment
- please call for IP classified versions

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.



LED SPOT Projector with interchangable C-mount lens

OMI OPTICS Engineering Ltd

TEL: +36 1 392 2278


LED Line Lights







LED Line Lights with single or dual wavelength



Typical Laser Patterns

LED Line Lights illuminate objects, signs, labels, or workpieces passing in front of a sensor e.g. a line-camera. Direct line illumination is a special lighting used in industrial machine vision automated inspections.

Specifications:

- LED light source projecting a straight line with high intensity
- plastic cylindrical lens
- white, blue, green, red or NIR light
- compact, anodized alu housing
- fixing with M5 screws
- working distance: 50-200 mm, focusable or fix
- > 50.000 h lifetime
- length of illuminated area: 50-300 mm
- width of illuminated area: 3-20 mm
- power requirement: 24 VDC
- available with power supply with optional trigger input
- continuous or strobe operation (depends on power supply)

LED Line Lights

Product number	Dimensions (mm)	Light emitting surface (mm)	Wavelength (nm)
3-015-000	250x60x20	250x10	White
3-015-750	90x87x20	80x15	NIR + White

Professional Laser Illuminations

Specifications:

- diffractive optics without moving parts, maintenance-free
- structured laser light
- focusable
- power requirement: 5V DC
- available with power supply with optional trigger input
- professional semiconductor laser chips
- designed to operate in harsh industrial environment
- robust, anodized aluminium housing
- available with adjustable fixing

Typical patterns:

- dot, dot-series
- line, parallel lines
- cross, grid
- circle, concentric circles
- custom patterns are also available on demand

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278

OMI OPTICS Engineering Ltd

ED Light Sources for Fibers







LED Light Sources for Fiber Optics



Focusable Optics

LED Light Sources for Fiber Optics offer longlife illumination for fiber optics application. Tens of thousands of hours lifetime, dimmable, constant color temperature.

Flexible or semi-rigid fibers are available with custom length and with focusable optics.

Specifications:


- nominal max. luminous flux: 1500 lm
- dimming with front panel knob or via Trigger Input
- dimensions: 250 x 220 x 117 mm
- power source: 230 V AC, max. 50 W
- short-driven external trigger
- thermal protection with internal heatswitch
- weight: 2,6 kg
- > 50.000 h lifetime
- available with custom wavelength LEDs

LED Light Source for Fiber Optics					
Product number	Dimensions (mm)	Fiber connection dimension	Fiber diameter		
3-650-000	250x220x117 mm	Ø14x37 mm	Ø6 mm		
3-650-500	250x220x117 mm	Ø8,4x30 mm	Ø1 mm		

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.

LED Matrix Lights



Typical dimensions



White LED Matrix Lights



NIR LED Matrix Lights

LED Matrix Lights illuminate objects, signs, labels or workpieces with light emitted by a large surface area. This kind of direct illumination offers high intensity for a wide range of application.

Specifications:

- white, UV, blue, green, red or NIR light
- power source: 12V DC or 24V DC
- available with power supply with optional trigger input
- continous or strobe operation (depends on power supply)
- > 50.000 h lifetime
- robust, anodized alu housing
- compact size
- fixing with M4 screw
- designed to operate in harsh industrial environment

LED Matrix Lights				
Product number	Dimensions (mm)	Light emitting surface (mm)	Wavelength (nm)	
3-005-000	40x20x22	32x16	640	
3-001-000	70x30x45	64x26	630	
3-002-000	70x30x45	64x26	880	
3-003-000	70x30x45	64x26	white	

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.

OMI OPTICS Engineering Ltd

LED Power Supplies



Power Supply with built in knob



Power Supply with multiple outputs



Power Supply with tigger input and multiple outputs

LED Power Supplies and Drivers are available in several versions depending on user requirements: dimmable, triggerable, with one or more outputs, typically with DIN rail mounting.

Because of the varied fields of applications, details must be specified when ordering.

Specifications:

- switched-mode circuits
- available dimmable with built in knob or analog signal
- available with external trigger input
- typical versions:
 - 12V DC or 24V DC input, constant current output
 - o 230V AC input, constant current ouput
 - 230V AC input, 5V DC, 12V DC or 24V DC output available with multiple outputs
- DIN rail mounting
- flickerless technology


LED Power Supplies

Product number	Input / Output	Dimming/Triggering
7-219-600	24 VDC / 24 VDC	trigger + knob
7-219-700	24 VDC / 12 VDC	trigger + knob
7-227-600	24 VDC / 700 mA	trigger + knob
7-227-700	24 VDC / 700 mA	trigger
7-235-600	24 VDC / 950 mA + 24 VDC	trigger
7-235-900	24 VDC / 1500 mA	built in knob

More standard and custom versions are available.

For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.


Optical Accessories



Optical microstructures for calibration



Chessboard calibration plate with back illumination



Optical mirrors



C-mount spacers

Optical microstructures for calibration

We offer optical microstructures for calibration and measurement purpose. Micrometer-range precision, microlitographic technology. Please call for custom figures and substrates. Large printed versions are available as well.

Optical Mirrors

We manufacture and refurbish front or rear surface aluminium coated mirrors.

Extension tubes, spacer rings

We manufacture and offer extension tubes and spacers for C-mount lenses and for other kind of industrial optics. Custom length and versions with electronically isolated threads are available as well.

Optical filters for Machine Vision

Low pass, high pass, bandpass, polarisation and other filters are available.


More standard and custom versions are available.


For specific wavelength, shape, power, dimension, housing etc. visit www.omi-optika.hu, send a message to info@omi-optika.hu or call +36-1-392-2278.



Optical filters

)MI OPTICS Engineering Ltd





High precision aperture for neutron imaging

Optical and optomechanical systems and devices

We design, develop, produce and install optical and optomechanical devices and equipments.

Please call for in-line machine vision equipments for noncontact quality inspection.

We design, develop and manufacture optomechanical devices for research and science.

Restoring and refurbishing optical devices

Restoring, repairing

We restore historical optical devices and instruments, achieving the original and functional condition: surveying instruments e.g. theodolites, old binoculars, astronomical telescopes etc. We repair, renew, restore and clean binoculars, riflescopes and other optical devices.

Refurbishing, modernization

We refurbish, functionally repair, renew and calibrate optical devices, instruments and tools by repairing or replacing the optical, mechanical and electrical components: industrial microscopes, optical instruments, projection microscopes etc.



PGAA – NIPS neutron tomograph



Refurbished X-Y measuring microscope



Renewed heliometer Fraunhoffer 1817

OMI OPTIKA Mérnökiroda Kft. info@omi-optika.hu JMI OPTICS Engineering Ltd.

Machine Vision Lenses









Machine

- Production
- Control
- Logistics

Vision

- Up to 12 MP
- Compact design
- Ultra-low distortion

Systems

- CMOSIS compatible
- 4K Board
- Infra-Red Solutions

Telecentric Lenses

Macro Optics

360° Optics







@

OMI OPTICS Engineering Ltd.

tel.: +36 1 392 2208

- LED megvilágítások és szűrők fluoreszcens alkalmazásokhoz
 - LED fényforrások száloptikai megvilágításhoz

 objektívek,szűrők, közgyűrűk, tükrök







A XXVI. Magyar Innovációs Nagydíj bírálóbizottsága

az OPTIKA Mérnökiroda Kft.-t

elismerésben részesíti a 2017. évben megvalósított

"Új fejlesztésű, multispektrális és fluoreszcens LED megvilágítások ipari képfeldolgozási feladatokhoz"

c. jelentős innovációért.

2018. március 28.



Zdvodle, t P(gł. Závodszky Péter akadémikus a Magyar Innovációs Alapítvány elnöke

Dr. Fakucs János J Magyar Innovációs Szövetség tisztb. elnöke,



- ipari objektívek akár 12 MP-ig alacsony torzítással





- SWIR objektívek
 - telecentrikusobjektívek







Mérnökiroda Kft. OMI OPTIKA Engineering Ltd. Hong April 1429.33

Hong April 1429.33 SKILLY, OKUTO SIKO KUN +36 1 392 2278 1135 +36 30 950 1135